

Microphone Preamplifier Power Supply

Model 2221

Larson
Davis



Typical Applications

- Powering precision microphones and preamplifiers
- Signal conditioning and amplification for use with recorders, data loggers, and frequency analyzers



Features

- Internal battery power with low power consumption
- 0 and 200 volt polarization voltage
- Selectable Flat (Z), A, and C-weighting
- 0 to 50 dB gain
- Both instantaneous and latching overload indicators
- LED indicators for output signal, internal battery voltage, and external power
- Drives long cables (500 foot), input and output
- High preamplifier current capability to drive Larson Davis PRM903 preamplifier with internal heater
- Compatible with ICP® powered transducers (using PRA951 adaptor)
- Recalls last active setup upon power-up

The Model 2221 provides the highly stable DC polarization voltage required by precision microphones along with low noise amplification enabling it to drive input and output cables as long as 500 feet. It is rugged, lightweight and will provide up to forty hours of continuous operation (with PRM902 Microphone Preamplifier) using six AA internal batteries. It can also provide sufficient current to power the PRM903 Microphone Preamplifier, which has an internal heater.

Model 2221 Microphone Preamplifier Power Supply

Technical Specifications

Frequency Response	(0 to 40 dB gain, 1 Vrms output)	10 Hz to 100 kHz (± 0.2 dB)			
	Flat (Z-weight)	2 Hz to 150 kHz (-3 dB)			
	Z, A and C-weight filters	Conform to IEC 61672-1:2002 "Sound Level Meters" Class 1			
	A-weight	20 Hz to 20 kHz (± 0.2 dB)			
	C-weight	10 Hz to 20 kHz (± 0.2 dB)			
Microphone bias voltage	0 and 200 Volts; ± 0.25 V				
Preamplifier supply	± 18 Volts				
Output signal weighting	Flat (Z), A and C-weighted				
Gain settings	0 to 40 dB in 10 dB steps, plus 0 to 10 dB vernier				
Maximum input level	18 Vpeak				
Maximum output current	25 mA				
Output noise	input shorted to ground, 20 Hz to 20 kHz	Gain	Flat (Z-wt)	A-wt	C-wt
		0	1.9 μ V	5.9 μ V	4.4 μ V
		20	7.8 μ V	20 μ V	6.6 μ V
Overload indicators	Instantaneous	Blinking LED			
	Latched	Solid LED, reset on keypad			
Operating temperature range	$<\pm 0.03$ dB @ 1 kHz	-40 to +60 °C (-40 to +140 °F)			
Humidity range	$<\pm 0.03$ dB @ 1 kHz	0 to 90% RH, non-condensing at 40 °C (104 °F)			
Dimension	Height	32.8 mm (1.29 in)			
	Width	104 mm (4.10 in)			
	Depth	204 mm (8.02 in)			
Connectors	Input	7-Pin LEMO 1B female			
	Output	BNC Female			
Weight	425 gram (15 oz)				
Power requirements	internal batteries	6 \times AA; 40 hrs with PRM902 preamp			
	external DC	10.5 to 30V; 65ma @ 12 V with PRM902 connector 2.5 \times 5.5 coax, center positive			
Power adaptor (provided)	Larson Davis PSA017; 115Vac to 9Vdc, 500mA				
Cable driving capability: 30 pF/ft cable	Length	14 Vpeak	4.2Vpeak	1.4Vpeak	
	250 ft	38 kHz	120 kHz	300 kHz	
	500 ft	19 kHz	62 kHz	180 kHz	
CE	CE-mark indicates compliance with the EMC Directive				

All values are at 20 °C, 50% RH, 12 V supply, <3 m (10 ft) cable, and a direct input from a 50 ohm generator, unless otherwise specified.

Accessories and Related Products

PRM902	½" Microphone Preamplifier
PRM903	½" Microphone Preamplifier with internal heater
CBL097	7-Pin LEMO to BNC cable, 6 ft
PSA021	230Vac to 9Vdc, 500mA power adaptor
PRA951-2	2 mA ICP® current source
PRA951-4	4 mA ICP® current source
CAL200	Class 1 acoustic calibrator 94/114 dB @ 1 kHz
CAL250	Class 1 acoustic calibrator 114 dB @ 250Hz

Input Connector Pinouts

Pin	Signal
1	No connection
2	Signal ground
3	Microphone polarization voltage 0 or 200 Volts
4	Signal input
5	No connection
6	Power supply positive voltage +18 Volts
7	Power supply negative voltage -18 Volts
Shell	Connected to Case ground



Larson Davis

A PCB Group Co.

Larson Davis, Inc. – Acoustic Test Products Group

1681 West 820 North, Provo, UT 84601-1341 USA

Toll Free: 888-258-3222 Phone: 801-375-0177 Fax: 801-375-0182

Email: marketing@larsondavis.com www.LarsonDavis.com

ICP is a registered trademark of PCB Group, Inc. All other trademarks are property of their respective owners. In the interest of constant product improvement, specifications are subject to change without notice.

© 2003 Larson Davis, Inc.

PRINTED IN U.S.A.

ATP-2221-1003/D0501.0011 REV B



dollenmeier

**Ingenieurbüro
Dollenmeier GmbH**

Regensbergstrasse 16

CH-8157 Dielsdorf

www.ibdoll.ch

Tel. 044 885 45 11

Fax 044 885 45 12