

ICP® PRESSURE SENSOR			Revision: F ECN #: 29920																																																																							
Model Number 138A25																																																																										
<table><tr><th colspan="2">ENGLISH</th><th colspan="2">SI</th><th></th></tr><tr><td rowspan="10">Performance Measurement Range(for ±5V output) Useful Overrange(for ± 10V output) Sensitivity(± 15 %) Maximum Pressure Resolution Resonant Frequency Rise Time(Reflected) Low Frequency Response(-5 %) Non-Linearity Environmental Temperature Range(Operating) Maximum Shock Electrical Output Polarity(Positive Pressure) Discharge Time Constant(at room temp) Excitation Voltage Constant Current Excitation Output Impedance Output Bias Voltage Physical Sensing Element Housing Material Electrical Connector Weight</td><td>25 kpsi</td><td>172,375 kPa</td><td>[1]</td><td rowspan="10">OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. N - Negative Output Polarity W - Water Resistant Cable NOTES: [1] Calibrated range to 20,000 psi. [2] For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias. [3] Typical. [4] Zero-based, least-squares, straight line method. [5] See PCB Declaration of Conformance PS023 for details.</td></tr><tr><td>50 kpsi</td><td>344,750 kPa</td><td>[2]</td></tr><tr><td>0.2 mV/psi</td><td>0.029 mV/kPa</td><td></td></tr><tr><td>50 kpsi</td><td>344,750 kPa</td><td>[3]</td></tr><tr><td>500 mpsi</td><td>3.5 kPa</td><td></td></tr><tr><td>≥ 1000 kHz</td><td>≥ 1000 kHz</td><td></td></tr><tr><td>≤ 1.5 μ sec</td><td>≤ 1.5 μ sec</td><td></td></tr><tr><td>2.5 Hz</td><td>2.5 Hz</td><td></td></tr><tr><td>≤ 2.0 % FS</td><td>≤ 2.0 % FS</td><td>[4]</td></tr><tr><td>0 to +100 °F</td><td>-17.8 to +37.8 °C</td><td></td></tr><tr><td>20,000 g pk</td><td>196,140 m/s² pk</td><td></td></tr><tr><td>Positive</td><td>Positive</td><td></td></tr><tr><td>≥ 0.2 sec</td><td>≥ 0.2 sec</td><td></td></tr><tr><td>20 to 30 VDC</td><td>20 to 30 VDC</td><td></td></tr><tr><td>2 to 20 mA</td><td>2 to 20 mA</td><td></td></tr><tr><td>≤ 100 ohm</td><td>≤ 100 ohm</td><td></td></tr><tr><td>8 to 14 VDC</td><td>8 to 14 VDC</td><td></td></tr><tr><td>Tourmaline</td><td>Tourmaline</td><td></td></tr><tr><td>Stainless Steel</td><td>Stainless Steel</td><td></td></tr><tr><td>10-32 Coaxial Jack</td><td>10-32 Coaxial Jack</td><td></td></tr><tr><td>0.75 oz</td><td>21.0 gm</td><td></td></tr></table>					ENGLISH		SI			Performance Measurement Range(for ±5V output) Useful Overrange(for ± 10V output) Sensitivity(± 15 %) Maximum Pressure Resolution Resonant Frequency Rise Time(Reflected) Low Frequency Response(-5 %) Non-Linearity Environmental Temperature Range(Operating) Maximum Shock Electrical Output Polarity(Positive Pressure) Discharge Time Constant(at room temp) Excitation Voltage Constant Current Excitation Output Impedance Output Bias Voltage Physical Sensing Element Housing Material Electrical Connector Weight	25 kpsi	172,375 kPa	[1]	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. N - Negative Output Polarity W - Water Resistant Cable NOTES: [1] Calibrated range to 20,000 psi. [2] For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias. [3] Typical. [4] Zero-based, least-squares, straight line method. [5] See PCB Declaration of Conformance PS023 for details.	50 kpsi	344,750 kPa	[2]	0.2 mV/psi	0.029 mV/kPa		50 kpsi	344,750 kPa	[3]	500 mpsi	3.5 kPa		≥ 1000 kHz	≥ 1000 kHz		≤ 1.5 μ sec	≤ 1.5 μ sec		2.5 Hz	2.5 Hz		≤ 2.0 % FS	≤ 2.0 % FS	[4]	0 to +100 °F	-17.8 to +37.8 °C		20,000 g pk	196,140 m/s² pk		Positive	Positive		≥ 0.2 sec	≥ 0.2 sec		20 to 30 VDC	20 to 30 VDC		2 to 20 mA	2 to 20 mA		≤ 100 ohm	≤ 100 ohm		8 to 14 VDC	8 to 14 VDC		Tourmaline	Tourmaline		Stainless Steel	Stainless Steel		10-32 Coaxial Jack	10-32 Coaxial Jack		0.75 oz	21.0 gm	
ENGLISH		SI																																																																								
Performance Measurement Range(for ±5V output) Useful Overrange(for ± 10V output) Sensitivity(± 15 %) Maximum Pressure Resolution Resonant Frequency Rise Time(Reflected) Low Frequency Response(-5 %) Non-Linearity Environmental Temperature Range(Operating) Maximum Shock Electrical Output Polarity(Positive Pressure) Discharge Time Constant(at room temp) Excitation Voltage Constant Current Excitation Output Impedance Output Bias Voltage Physical Sensing Element Housing Material Electrical Connector Weight	25 kpsi	172,375 kPa	[1]	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. N - Negative Output Polarity W - Water Resistant Cable NOTES: [1] Calibrated range to 20,000 psi. [2] For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias. [3] Typical. [4] Zero-based, least-squares, straight line method. [5] See PCB Declaration of Conformance PS023 for details.																																																																						
	50 kpsi	344,750 kPa	[2]																																																																							
	0.2 mV/psi	0.029 mV/kPa																																																																								
	50 kpsi	344,750 kPa	[3]																																																																							
	500 mpsi	3.5 kPa																																																																								
	≥ 1000 kHz	≥ 1000 kHz																																																																								
	≤ 1.5 μ sec	≤ 1.5 μ sec																																																																								
	2.5 Hz	2.5 Hz																																																																								
	≤ 2.0 % FS	≤ 2.0 % FS	[4]																																																																							
	0 to +100 °F	-17.8 to +37.8 °C																																																																								
20,000 g pk	196,140 m/s² pk																																																																									
Positive	Positive																																																																									
≥ 0.2 sec	≥ 0.2 sec																																																																									
20 to 30 VDC	20 to 30 VDC																																																																									
2 to 20 mA	2 to 20 mA																																																																									
≤ 100 ohm	≤ 100 ohm																																																																									
8 to 14 VDC	8 to 14 VDC																																																																									
Tourmaline	Tourmaline																																																																									
Stainless Steel	Stainless Steel																																																																									
10-32 Coaxial Jack	10-32 Coaxial Jack																																																																									
0.75 oz	21.0 gm																																																																									
<table><tr><td>Entered: <i>Let</i></td><td>Engineer: <i>BAB</i></td><td>Sales: <i>KWM</i></td><td>Approved: <i>EPS</i></td><td>Spec Number:</td></tr><tr><td>Date: <i>1-8-09</i></td><td>Date: <i>12-19-08</i></td><td>Date: <i>12-22-08</i></td><td>Date: <i>1-7-09</i></td><td>138-1250-80</td></tr></table>					Entered: <i>Let</i>	Engineer: <i>BAB</i>	Sales: <i>KWM</i>	Approved: <i>EPS</i>	Spec Number:	Date: <i>1-8-09</i>	Date: <i>12-19-08</i>	Date: <i>12-22-08</i>	Date: <i>1-7-09</i>	138-1250-80																																																												
Entered: <i>Let</i>	Engineer: <i>BAB</i>	Sales: <i>KWM</i>	Approved: <i>EPS</i>	Spec Number:																																																																						
Date: <i>1-8-09</i>	Date: <i>12-19-08</i>	Date: <i>12-22-08</i>	Date: <i>1-7-09</i>	138-1250-80																																																																						
 [5] All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Group, Inc.																																																																										
 Phone: 716-684-0001 Fax: 716-686-9129 E-Mail: pressure@pcb.com 3425 Walden Avenue, Depew, NY 14043																																																																										