



Model Number 3711E1125G		DC RESPONSE ACCELEROMETER		Revision: A ECN #: 44033
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Sensitivity(± 5 %)	80 mV/g	8.15 mV/(m/s ²)		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Measurement Range	± 25 g pk	± 245.2 m/s ² pk		
Frequency Range(± 3 dB)	0 to 1500 Hz	0 to 1500 Hz	[2]	
Frequency Range(± 3 dB)	0 to 750 Hz	0 to 750 Hz	[5]	
Phase Response(100 Hz)	<10 °	<10 °		
Broadband Resolution(0.5 to 100 Hz)	.5 mg rms	.0049 m/s ² rms	[2]	
Non-Linearity	≤ 1 %	≤ 1 %	[6]	
Transverse Sensitivity	≤ 5 %	≤ 5 %		
Environmental				
Overload Limit(Shock)	± 5000 g pk	± 49,050 m/s ² pk		
Temperature Range(Operating)	-65 to +250 °F	-54.0 to +121 °C		
Temperature Range(Storage)	-65 to +250 °F	-54.0 to +121 °C		
Temperature Coefficient of Sensitivity	± 3 %	± 3 %	[3]	
Zero g Offset Temperature Coefficient	± 2 % FSO	± 2 % FSO	[3][4]	
Base Strain Sensitivity(Measured at 250 µε)	.001 g/µε	.01 (m/s ²)/µε	[2]	
Magnetic Sensitivity	100 µg/gauss	9.8 (m/s ²)/Tesla	[2]	
Electrical				
Excitation Voltage	6 to 30 VDC	6 to 30 VDC		
Current Consumption	≤ 30 mA	≤ 30 mA		
Output Impedance	≤ 120 Ohm	≤ 120 Ohm		
Offset Voltage(0 g)	80 to +80 mVDC	80 to +80 mVDC	[1]	
Spectral Noise(1 to 100 Hz)	100 µg/√Hz	981 (µm/sec ²)/√Hz	[2]	
Electrical Isolation(Case)	>10 ⁸ Ohm	>10 ⁸ Ohm		
Physical				
Housing Material	Titanium	Titanium		
Sealing	Hermetic	Hermetic		
Size (Height x Length x Width)	0.45 in x 0.85 in x 0.85 in	11.4 mm x 21.6 mm x 21.6 mm		
Weight	0.58 oz	16.3 gm		
Electrical Connector	4-Pin	4-Pin		
Electrical Connection Position	Side	Side		
Mounting	Through Holes (2)	Through Holes (2)		
				
<p>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Group, Inc.</p>				
<p>NOTES: [1]Offset tolerance is based on 10 ft of 010 test cable. [2]Typical. [3]-65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C) [4]FSO = Full Scale Output over the Measurement Range (4VDC). [5]Minimum, verified with Calibration data. [6]Least-squares, straight line method, % FSO. [7]See PCB Declaration of Conformance PS027 for details.</p>				
<p>SUPPLIED ACCESSORIES: Model 080A152 Easy Mount Clip (1) Model 081A113 Mounting screw assembly (2) Model ACS-145 Phase and Amplitude Calibration from 2 Hz to ±3 dB of frequency range (1) Model M081A113 Mounting screw assembly (2)</p>				
Entered: AP	Engineer: JJD	Sales: RWM	Approved: NJF	Spec Number:
Date: 3/27/2015	Date: 3/27/2015	Date: 3/27/2015	Date: 3/27/2015	59598
				
<p>3425 Walden Avenue, Depew, NY 14043</p>				
<p>Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com</p>				